



The N3-070 is designed to clearly define the step edge and prevent slips and falls in all weather conditions.

COMPLIANCE

Complies with BCA Code on Accessibility in Built Environment 2013 Clause 4.11.2.2 that required all steps shall be fitted with non-slip strips between 50 mm and 65 mm in width with permanent contrasting colours.

Compliance to Workplace Safety and Health Act in preventing slips and falls in Workplace.

PERFORMANCE

The Step Edge Contrast Strip is suitable for use indoors and outdoors. The non-slip material provides all weather protection from slips and falls.

Anti-slip Properties – AS/NZ 4586-2004 Classification: FV (classified as P5 in AS 4586-2013)

SUPPLY

The products are available in 2.40 metre or 3.0 metre. Cut lengths can be fabricated on site or in factory.

COMPOSITION

Ecoglo N3-070 Non-Slip Strip, Black 51.0 mm width is adhesively fixed into the extrusion. The non-slip strip N3-070 is manufactured from extruded 6060T5 aluminium section. Silicon Carbide non-slip materials are embedded in thermoset polyester carriers to integrally bond the active ingredients into the aluminium following curing at high temperature.

INSTALLATION

The N3-070 Step Edge Contrast Strip utilizes exposed fixers to confirm sound installation for ongoing maintenance inspections and compliance.

The Step Edge Contrast Strip can be surface mounted on all smooth surfaces.

The Step Edge Contrast Strip also can be recessed into the groove of timber or tiles.



Installation is a simple process using fixers and adhesive.

The N3-070 can also be used with Ecoglo Flat Nosings that require a 51.0 mm insert.

Recommended installation adhesive is Bostik Seal N Flex. Recommended installation plug is Fischer Plug SX.

Contact

Ecoglo Pte Ltd

**111 North Bridge Road #17-06 Peninsula Plaza
Singapore 179098**

Phone: 6858 3530 Fax: 6826 4138

email: info@ecoglo.sg URL: www.ecoglo.sg